



Outdoor Floor Standing Signage

43",55",65",75",86"

Stand Bold. Shine Outdoors.

Weatherproof and built to impress, this outdoor floor standing signage is perfect for delivering high-impact visuals in open spaces. Its durable build and bright display ensure visibility, rain or shine.

Benefits

- Enhanced Engagement
- Real-Time Updates
- Cost Efficiency
- Space Efficiency
- Increased Visibility
- Improved Collaboration



High Brightness
LCD



Touch
Optional



Supports Android
& Windows Os



Multi-size
Display



Remote
Control



Power-efficient with
standby mode

Specification						
Electric/Heat dissipation	Waterproof loudspeaker	Waterproof high quality 2*10W speaker				
	Power supply	Industrial power supply from Meanwell				
	SPD	Level 3 lightning protection				
	leakage protector	Protection current 30mA				
	Timer	Set the switching time by day and week				
	Ventilation	High precision filter, filter 99.6% dust				
	AFAns	High quality speed-regulating AFAn				
Structure	The housing material shell	1.5mm galvanized steel plate, surface spray outdoor special powder, protection capacity of more than 7 years.				
	Glass	Adopt 5mm high light transmittance AG glass				
	Waterproof structure	Door design waterproof structure, seal with outdoor rubber strip, meet IP55 protection level				
		43"	55"	65"	75"	86"
LCD Panel	Resolution	1920*1080	1920*1080	3840*2160	3840*2160	3840*2160
	Backlight	LED				
	Brightness	2500nits, 3000 nits (Optional)				
	Contrast Ratio	1200:1				
	Color Depth	8 bits				
	Response Time	8 ms (typ)				
	Viewing Angle	178° / 178°				
	Light Life Time	50,000 hrs (typ.)				
Power	Power Supply	Internal				
	Rated Voltage	100 V ~ 240 V, 50 Hz / 60 Hz				
	Power Consumption	400 W (max)	450 W (max)	560W	650W	800W
User Interface	Language	English				
	Dimming Control (DCR)	Yes				
	Ambient Light Sensor	Yes				
	Internal Temperature Sensor	Yes				
Enviornment	Operating Temperature	-10° C ~ 60° C				
	Storage Temperature	-20° C ~ 60° C				
	Humidity	10% ~ 80% RH Non-condensing				
Internal Player	Processor	Quad-core Cortex-A55 up to 2.0GHz				
	Main memory interAFace	2GB DDR3				
	Graphics	Mail-G52				
	Storage (FDM)	EMMC 16GB				
	Multimedia	H.264 encoder/decoder, MPEG-1/2/4, H.263,H.264 MVC, AVS, VC-1, VP8/6, RV				
	IO ports	USB3.0*2, micro SD slot x1				
	Operating system	Windows, Android (Optional)				
	Network	WLAN 802.11 b/g/n (2.4GHz) ,RJ45				
Mechanical Specs	Cabinet Color	Black / White				
	Dimension (LxHxD)	730*350*1950mm	850*500*2100mm	970*500*2450mm	1246*500*2470mm	2825*1284*300mm