

## **SLIMAURA**

## Slim and sleek design for designer wall

The SLIMAURA Slim-fit Wall Mount offers a sleek, flush finish—perfect for modern interiors. Its ultra-slim profile blends seamlessly with any space, turning digital displays into a natural part of the wall.



## Flexible Sizes & Shapes

We now offer a range of sizes, from compact to large models, with no long wait times or extra costs. Choose from various installation methods to suit your space and needs, and create personalized layouts with customizable shapes.



Splicing Types

Conventional splicing

Vertical screen splicing

Horizonal screen splicing

I rregular screen splicing

















www.onandsys.com

Specifications		
LCD Panel	Sizes	21.5", 23.8", 27", 32", 43", 55", 65", 75", 85"
	LCD Type	TFT-LCD
	Display colo	16.7M
	Brightness	500 nits
	Contrast	3000:1
	View-angle(up/downfleft/right)	89°/89°/89°
	View-distance mi	1~8 m
	Response lime	8ms
	Field Frequency	50/60 Hz
	Q5D Language	English
	Touch Style	Touch Optional
Computer configuration	CPU	T972 Quad Core 1.9 GHz CPU
	RAM	2GB,4GB,8GB, 16GB (Optional)
	HARD DISK	32GB, 64GB, 128GB (Optional)
	Interfaces	HDMI IN, USB etc.
	WIFISLAN	YES
	OS	Android 9.0 above
	4G network	No, can be added
Power	Power	AC100V - 240V, 50/60Hz
	The maximum power	135W
	Standby power	<1W
	Speakers	Stereo
Environment	Operating temperature	0°C-45°C
	Operation Humidity	10-90%
	Storage temperature	-20°C-60°C
	Life	50000hrs
Other	Frame material	Aluminum metal
	Installation	Landscape/portrait
	Rango of application	Indoor